

HP MSR50 Router Series



Key features

- High-performance, modular LAN/WAN router
- Converged routing, switching, wireless, voice, and security
- Third-party applications and virtualized services platform
- Embedded encryption, firewall, and other security features
- High reliability, with available dual power supplies and hot-swappable modules

Product overview

The HP MSR50 Router Series are components of the HP FlexBranch solution, which is part of the HP FlexNetwork Architecture.

These routers are designed for large branch offices, regional offices, and enterprise deployments that require high-performance converged routing, switching, wireless, security, voice, and virtualized applications.

The MSR50 Series has a rich set of modular WAN, LAN, and voice interface connectivity options, as well as embedded hardware-based encryption and voice processing. With optional Open Application Architecture Platform (OAP) modules, it can deliver VMware vSphere, an industry-leading virtualization platform that integrates third-party applications with the router.

Features and benefits

Quality of service (QoS)

- Traffic policing
 - Supports Committed Access Rate (CAR) and line rate
- Congestion management
 - Supports FIFO, PQ, CQ, WFQ, CBQ, and RTPQ
- Weighted random early detection (WRED)/random early detection (RED)
 - Delivers congestion avoidance capabilities using queue management algorithms
- Other QoS technologies
 - Support traffic shaping, FR QoS, MPLS QoS, and MP QoS/LFI

Management

- Management interface control
 - Provides management access through modem port and terminal interface; provides access through terminal interface, TELNET or SSH
- Industry-standard CLI with a hierarchical structure
 - Reduces training time and expenses, and increases productivity in multivendor installations
- Management security
 - Restricts access to critical configuration commands; offers multiple privilege levels with password protection; ACLs provide telnet and SNMP access; local and remote syslog capabilities allow logging of all access
- SNMPv1, v2, and v3
 - Provide complete support of SNMP; provide full support of industry-standard management information base (MIB) plus private extensions; SNMPv3 supports increased security using encryption
- Remote monitoring (RMON)
 - Uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- FTP, TFTP, and SFTP support
 - Offer different mechanisms for configuration updates; FTP allows bidirectional transfers over a TCP/IP network; trivial FTP (TFTP) is a simpler method using User Datagram Protocol (UDP); Secure File Transfer Protocol (SFTP) runs over an SSH tunnel to provide additional security
- Debug and sampler utility
 - Supports ping and traceroute for both IPv4 and IPv6
- Network Time Protocol (NTP)
 - Synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time

- Information center

Provides a central repository for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules

- Network Quality Analyzer (NQA)

Analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays; allows network manager to determine overall network performance and diagnose and locate network congestion points or failures

Connectivity

- High-density port connectivity

Provides up to 10 interface module slots and up to 90 Fast Ethernet ports

- Multiple WAN and LAN interfaces

Provide a traditional link with E3, T3, E1, T1, ADSL, ADSL2, ADSL2+, G.SHDSL, OC-3, POS, ATM, and ISDN/AM backup; deliver high-density Ethernet access with WAN Fast Ethernet/Gigabit Ethernet, LAN Fast Ethernet, and PoE; offer mobility access with IEEE 802.11b/g/n Wi-Fi and 3G

- 3G access support

Provides 3G wireless access for primary or backup connectivity via a 3G SIC module certified on various cellular networks; optional carrier 3G USB modems are available

- Ideal IP telephony solutions

Support FXO, FXS, T1, E1, and BRI in various densities; provide Web browser-based administration, Smart Dial Routing, FXS and FXO 1:1 binding for all ports, Power to Escape to PSTN when IP failures occur, and Enhanced Local MSR Survivability

- Flexible port selection

Provides a combination of fiber and copper interface modules, 100/1000BASE-X auto-speed selection, and 10/100/1000BASE-T auto-speed detection plus auto-duplex and MDI/MDI-X

- Packet storm protection

Protects against broadcast, multicast, or unicast storms with user-defined thresholds

- Loopback

Supports internal loopback testing for maintenance purposes and an increase in availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility

Performance

- Excellent forwarding performance

Provides forwarding performance up to 800 Kpps/1,280 Kpps (for two kinds of engines); meets current and future bandwidth-intensive application demands of enterprise businesses

- Powerful encryption capacity

Includes embedded hardware encryption accelerator to improve encryption performance

- Flexible chassis selection

Offers a choice of four or six FIC slot routers, meeting different requirements on enterprise branches

Resiliency and high availability

- Hot-swappable modules

Facilitates the replacement of hardware interface modules without impacting the traffic flow through the system

- Dual internal power supply

Provides high reliability

- Virtual Router Redundancy Protocol (VRRP)

Allows groups of two routers to back each other up dynamically to create highly available routed environments; supports VRRP load balancing

Layer 2 switching

- Spanning Tree Protocol (STP)

Supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)

- Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping

Control and manage the flooding of multicast packets in a Layer 2 network

- Port mirroring

Duplicates port traffic (ingress and egress) to a local or remote monitoring port

- VLANs

Support up to 4,094 ports or IEEE 802.1Q-based VLANs

- sFlow

Allows traffic sampling

Layer 3 services

- Address Resolution Protocol (ARP)

Determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network

- User Datagram Protocol (UDP) helper

Redirects UDP broadcasts to specific IP subnets to prevent server spoofing

- Dynamic Host Configuration Protocol (DHCP)

Simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

Layer 3 routing

- Static IPv4 routing

Provides simple manually configured IPv4 routing

- Routing Information Protocol (RIP)

Uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection

- Open Shortest Path First (OSPF)

Delivers faster convergence; uses this link-state routing Interior Gateway Protocol (IGP), which supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery

- Border Gateway Protocol 4 (BGP-4)

Delivers an implementation of the Exterior Gateway Protocol (EGP) utilizing path vectors; uses TCP for enhanced reliability for the route discovery process; reduces bandwidth consumption by advertising only incremental updates; supports extensive policies for increased flexibility; scales to very large networks

- Intermediate system to intermediate system (IS-IS)

Uses a path vector Interior Gateway Protocol (IGP), which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)

- Static IPv6 routing

Provides simple manually configured IPv6 routing

- Dual IP stack

Maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design

- Routing Information Protocol next generation (RIPng)
Extends RIPv2 to support IPv6 addressing
- OSPFv3
Provides OSPF support for IPv6
- BGP+
Extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- IS-IS for IPv6
Extends IS-IS to support IPv6 addressing
- IPv6 tunneling
Allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels; is an important element for the transition from IPv4 to IPv6
- Multiprotocol Label Switching (MPLS)
Uses BGP to advertise routes across Label Switched Paths (LSPs), but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, which reduces complexity and increases performance; supports graceful restart for reduced failure impact; supports LSP tunneling and multilevel stacks
- Multiprotocol Label Switching (MPLS) Layer 3 VPN
Allows Layer 3 VPNs across a provider network; uses MBGP to establish private routes for increased security; supports RFC RFC2547 multiple autonomous system VPNs for added flexibility; supports IPv6 MPLS VPN
- Multiprotocol Label Switching (MPLS) Layer 2 VPN
Establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS Label Distribution Protocol (LDP); requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols; uses no routing information for increased security; supports Circuit Cross Connect (CCC), Static Virtual Circuits (SVCs), Martini draft, and Kompella-draft technologies
- Policy routing
Allows custom filters for increased performance and security; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies

Security

- Access control list (ACL)

Supports powerful ACLs for both IPv4 and IPv6; ACLs are used for filtering traffic to prevent unauthorized users from accessing the network, or for controlling network traffic to save resources; rules can either deny or permit traffic to be forwarded; rules can be based on a Layer 2 header or a Layer 3 protocol header; rules can be set to operate on specific dates or times

- Media access control (MAC) authentication

Provides simple authentication based on a user's MAC address; supports local or RADIUS-based authentication

- Terminal Access Controller Access-Control System (TACACS+)

Delivers an authentication tool using TCP with encryption of the full authentication request, providing additional security

- Network login

Standard IEEE 802.1X allows authentication of multiple users per port

- RADIUS

Eases security access administration by using a password authentication server

- Network address translation (NAT)

Supports one-to-one NAT, many-to-many NAT, and NAT control, enabling NAT-PT to support multiple connections; supports blacklist in NAT/NAT-PT, a limit on the number of connections, session logs, and multi-instances

- Secure shell (SSHv2)

Uses external servers to safely log in to a remote device or the router from a remote location; with authentication and encryption, it protects against IP spoofing and plain text password interception; increases the security of SFTP transfers

- Unicast Reverse Path Forwarding (URPF)

Allows normal packets to be forwarded correctly, but discards the attaching packet due to lack of reverse path route or incorrect inbound interface; prevents source spoofing and distributed attacks

- IPSec VPN

Supports DES, 3DES, and AES 128/192/256 encryption, and MD5 and SHA-1 authentication

- Dynamic Virtual Private Network (DVPN)

Collects, maintains, and distributes dynamic public addresses through the VPN Address Management (VAM) protocol, making VPN establishment available between enterprise branches that use dynamic addresses to access the public network; compared to traditional VPN technologies, DVPN technology is more flexible and has richer features, such as NAT traversal of DVPN packets, AAA identity authentication, IPSec protection of data packets, and multiple VPN domains

Convergence

- Internet Group Management Protocol (IGMP)

Utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks; supports IGMPv1, v2, and v3

- Protocol Independent Multicast (PIM)

Defines modes of Internet IPv4 and IPv6 multicasting to allow one-to-many and many-to-many transmission of information; supports PIM Dense Mode (DM), Sparse Mode (SM), and Source-Specific Mode (SSM)

- Multicast Source Discovery Protocol (MSDP)

Allows multiple PIM-SM domains to interoperate; is used for interdomain multicast applications

- Multicast Border Gateway Protocol (MBGP)

Allows multicast traffic to be forwarded across BGP networks and kept separate from unicast traffic

Integration

- Open Application Architecture (OAA)

Provides high-performance application-specific modules fully integrated with the switching architecture; uses the chassis high-speed backplane to access network-related data; increases performance, reduces costs, and simplifies network management

- Embedded NetStream

Improves traffic distribution using powerful scheduling algorithms, including Layer 4 to 7 services; monitors the health status of servers and firewalls

- Embedded VPN firewall

Provides enhanced stateful packet inspection and filtering; delivers advanced VPN services with Triple DES (3DES) and Advanced Encryption Standard (AES) encryption at high performance and low latency, Web content filtering, and application prioritization and enhancement

Additional information

- OPEX savings

Simplify and streamline deployment, management, and training with a common operating system, thereby cutting costs as well as reducing the risk of human errors associated with having to manage multiple operating systems across different platforms and network layers

- High reliability

Provides a state-of-the-art unified code base

- Faster time to market

Allows new and custom features to be brought rapidly to market through engineering efficiencies, delivering better initial and ongoing stability

- Green initiative support

Provides support for RoHS and WEEE regulations

Product architecture

- Ideal multiservice platform

Provides a WAN router, Ethernet switch, wireless LAN, 3G WAN, firewall, VPN, and SIP/voice gateway all in one box

- High-density voice interfaces

Provide flexible analog and digital voice interface options for easy integration within a wide range of deployments

- Embedded service modules for security and voice Embedded Voice Co-Processing Modules (VCPMs) and Voice

Processing Modules (VPMs) accommodate digital signal processor (DSP) modules for voice packet processing; embedded hardware encryption modules, Standard Network Data Encryption (SNDE) cards, and Advanced Network Data Encryption (ANDE) cards do not occupy I/O slots

- HP Open Application Platform (OAP) and virtualization

Are available on HP MSR Open Architecture Platform (OAP) module with VMware vSphere; offer an industry-leading virtualization platform, which integrates third-party applications with the MSR Router Series; provide application and services flexibility; deliver the potential functionality of multiple devices, creating capital and operational expense savings, and lasting investment protection

- USB interface

Uses USB memory disk to download and upload configuration files; supports an external USB 3G modem for a 3G WAN uplink

- Flexible modular design

Includes multiple types of modules that meet different requirements, such as HP Router Smart Interface Cards (SICs), which are small and cost-effective modules; multi-functional interface modules (MIMs), which are more high-density and affordable modules; HP Router Flexible Interface Cards (FICs), which provide high reliability and are hot-swappable; double-width modules, which provide high density

- SIP trunk

The SIP trunk link can carry multiple concurrent calls, and the carrier authenticates only the link, rather than carrying each SIP call on this link

Warranty and support

- 1-year warranty

Advance hardware replacement with 10-calendar-day delivery (available in most countries)

- Electronic and telephone support

Limited electronic and business-hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to hp.com/networking/warrantysummary

- Software releases

To find software for your product, refer to hp.com/networking/support; for details on the software releases available with your product purchase, refer to hp.com/networking/warrantysummary

HP MSR50 Series

Specifications



	HP MSR50-40 Router (JD433A)	HP MSR50-60 Router (JF231A)
I/O ports and slots	4 FIC slots	6 FIC slots
Physical characteristics		
Dimensions	17.17(w) x 16.69(d) x 5.16(h) in (43.6 x 42.4 x 13.1 cm) (3U height)	17.17(w) x 16.69(d) x 6.89(h) in (43.6 x 42.4 x 17.5 cm) (4U height)
Weight	39.68 lb (18 kg)	44.09 lb (20 kg)
Memory and processor	RISC @ 1700 MHz, 1 GB DDR SDRAM, 256 MB compact flash RISC @ 833 MHz, 512 MB DDR SDRAM, 256 MB compact flash	RISC @ 1700 MHz, 1 GB DDR SDRAM, 256 MB compact flash RISC @ 833 MHz, 512 MB DDR SDRAM, 256 MB compact flash
Mounting and enclosure	Mounts in an EIA-standard 19 in. telco rack	Mounts in an EIA-standard 19 in. telco rack
Performance		
Throughput	up to 1280 Kpps (64-byte packets)	up to 1280 Kpps (64-byte packets)
Routing/Switching capacity	3 Gbps	3 Gbps
Routing table size	100000 entries (IPv4), 100000 entries (IPv6)	100000 entries (IPv4), 100000 entries (IPv6)
Environment		
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	5% to 90%, noncondensing	5% to 90%, noncondensing
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	5% to 90%, noncondensing	5% to 90%, noncondensing
Electrical characteristics		
Frequency	50/60 Hz	50/60 Hz
Maximum heat dissipation	1194 BTU/hr (1259.67 kJ/hr)	1194 BTU/hr (1259.67 kJ/hr)
AC voltage	100 - 240 VAC	100 - 240 VAC
Maximum power rating	350 W	350 W
PoE power	500 W	500 W
	Note Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS).	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS).
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03; FDA 21 CFR Subchapter J	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03; FDA 21 CFR Subchapter J

	HP MSR50-40 Router (JD433A)	HP MSR50-60 Router (JF231A)
Emissions	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001
Telecom	FCC part 68; CS-03	FCC part 68; CS-03
Management	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
Notes	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (IEEE 802.11b/g, 802.11b/g/n, etc.) in the European Union. SIC and DSIC modules can only be used with the HP MSR50 Main Processing Unit (JD653A).	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (IEEE 802.11b/g, 802.11b/g/n, etc.) in the European Union. SIC and DSIC modules can only be used with the HP MSR50 Main Processing Unit (JD653A).
Services	<p>3-year, parts only, global next-day advance exchange (UX166E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UX167E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UX170E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UX173E)</p> <p>3-year, 24x7 SW phone support, software updates (UX176E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR546E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UX168E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UX171E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX174E)</p> <p>4-year, 24x7 SW phone support, software updates (UX177E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UX169E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UX172E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX175E)</p> <p>5-year, 24x7 SW phone support, software updates (UX178E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UX179E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UX180E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UX181E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR544E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR548E)</p> <p>1-year, 24x7 software phone support, software updates (HR547E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, parts only, global next-day advance exchange (UX166E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UX167E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UX170E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UX173E)</p> <p>3-year, 24x7 SW phone support, software updates (UX176E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR546E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UX168E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UX171E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX174E)</p> <p>4-year, 24x7 SW phone support, software updates (UX177E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UX169E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UX172E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX175E)</p> <p>5-year, 24x7 SW phone support, software updates (UX178E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UX179E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UX180E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UX181E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR544E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR548E)</p> <p>1-year, 24x7 software phone support, software updates (HR547E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

HP MSR50 Series

Specifications (continued)



	HP MSR50-40 DC Router (JF285A)	HP MSR50-60 DC Router (JF640A)
I/O ports and slots	4 FIC slots	6 FIC slots
Physical characteristics		
Dimensions	17.17(w) x 16.69(d) x 5.16(h) in (43.6 x 42.4 x 13.1 cm) (3U height)	17.17(w) x 16.69(d) x 6.89(h) in (43.6 x 42.4 x 17.5 cm) (4U height)
Weight	39.68 lb (18 kg)	44.09 lb (20 kg)
Memory and processor	RISC @ 1700 MHz, 1 GB DDR SDRAM, 256 MB compact flash RISC @ 833 MHz, 512 MB DDR SDRAM, 256 MB compact flash	RISC @ 1700 MHz, 1 GB DDR SDRAM, 256 MB compact flash RISC @ 833 MHz, 512 MB DDR SDRAM, 256 MB compact flash
Mounting and enclosure	Mounts in an EIA-standard 19 in. telco rack	Mounts in an EIA-standard 19 in. telco rack
Performance		
Throughput	up to 1280 Kpps (64-byte packets)	up to 1280 Kpps (64-byte packets)
Routing/Switching capacity	3 Gbps	3 Gbps
Routing table size	100000 entries (IPv4), 100000 entries (IPv6)	100000 entries (IPv4), 100000 entries (IPv6)
Environment		
Operating temperature	32°F to 104°F (0°C to 40°C)	32°F to 104°F (0°C to 40°C)
Operating relative humidity	5% to 90%, noncondensing	5% to 90%, noncondensing
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	5% to 90%, noncondensing	5% to 90%, noncondensing
Electrical characteristics		
Maximum heat dissipation	1194 BTU/hr (1259.67 kJ/hr)	1194 BTU/hr (1259.67 kJ/hr)
Maximum power rating	350 W	350 W
PoE power	500 W	500 W
	Note Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS).	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03; FDA 21 CFR Subchapter J	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03; FDA 21 CFR Subchapter J

	HP MSR50-40 DC Router (JF285A)	HP MSR50-60 DC Router (JF640A)
Emissions	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001	EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001
Telecom	FCC part 68; CS-03	FCC part 68; CS-03
Management	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
Notes	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (IEEE 802.11b/g, 802.11b/g/n, etc.) in the European Union. SIC and DSIC modules can only be used with the HP MSR50 Main Processing Unit (JD653A).	The HP 3G Wireless GSM/WCDMA WAN SIC Module (JF820A) is not approved for use in the same chassis as a Wi-Fi interface (IEEE 802.11b/g, 802.11b/g/n, etc.) in the European Union. SIC and DSIC modules can only be used with the HP MSR50 Main Processing Unit (JD653A).
Services	<p>3-year, parts only, global next-day advance exchange (UX166E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UX167E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UX170E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UX173E)</p> <p>3-year, 24x7 SW phone support, software updates (UX176E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR546E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UX168E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UX171E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX174E)</p> <p>4-year, 24x7 SW phone support, software updates (UX177E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UX169E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UX172E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX175E)</p> <p>5-year, 24x7 SW phone support, software updates (UX178E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UX179E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UX180E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UX181E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR544E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR548E)</p> <p>1-year, 24x7 software phone support, software updates (HR547E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

Standards and Protocols

(applies to all products in series)

BGP	RFC 1163 Border Gateway Protocol (BGP) RFC 1267 Border Gateway Protocol 3 (BGP-3) RFC 1657 Definitions of Managed Objects for BGPv4 RFC 1771 BGPv4	RFC 1772 Application of the BGP RFC 1773 Experience with the BGP-4 Protocol RFC 1774 BGP-4 Protocol Analysis RFC 1997 BGP Communities Attribute	RFC 1998 An Application of the BGP Community Attribute in Multi-home Routing RFC 2385 BGP Session Protection via TCP MD5 RFC 2439 BGP Route Flap Damping
Denial of service protection	CPU DoS Protection	Rate Limiting by ACLs	
Device management	RFC 1305 NTPv3	RFC 1945 Hypertext Transfer Protocol—HTTP/1.0	RFC 2452 MIB for TCP6 RFC 2454 MIB for UDP6
General protocols	IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1w Rapid Reconfiguration of Spanning Tree RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 791 IP RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 854 TELNET RFC 855 Telnet Option Specification RFC 856 TELNET RFC 858 Telnet Suppress Go Ahead Option RFC 894 IP over Ethernet RFC 925 Multi-LAN Address Resolution RFC 950 Internet Standard Subnetting Procedure RFC 959 File Transfer Protocol (FTP) RFC 1006 ISO transport services on top of the TCP: Version 3 RFC 1027 Proxy ARP RFC 1034 Domain Concepts and Facilities RFC 1035 Domain Implementation and Specification RFC 1042 IP Datagrams RFC 1058 RIPv1 RFC 1071 Computing the Internet Checksum RFC 1091 Telnet Terminal-Type Option RFC 1122 Host Requirements RFC 1141 Incremental updating of the Internet checksum RFC 1142 OSI IS-IS Intra-domain Routing Protocol	RFC 1701 Generic Routing Encapsulation RFC 1702 Generic Routing Encapsulation over IPv4 networks RFC 1721 RIP-2 Analysis RFC 1722 RIP-2 Applicability RFC 1723 RIP v2 RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLsw RIG: DLsw Closed Pages, DLsw Standard Version 1 RFC 1812 IPv4 Routing RFC 1829 The ESP DES-CBC Transform RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses RFC 1878 Variable Length Subnet Table for IPv4 RFC 1944 Benchmarking Methodology for Network Interconnect Devices RFC 1973 PPP in Frame Relay RFC 1974 PPP Stac LZS Compression Protocol RFC 1990 The PPP Multilink Protocol (MP) RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) RFC 2091 Trigger RIP RFC 2131 DHCP RFC 2132 DHCP Options and BOOTP Vendor Extensions RFC 2166 APPN Implementer's Workshop Closed Pages Document DLsw v2.0 Enhancements RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification RFC 2280 Routing Policy Specification Language (RPSL) RFC 2284 EAP over LAN RFC 2338 VRRP	RFC 3022 Traditional IP Network Address Translator (Traditional NAT) RFC 3027 Protocol Complications with the IP Network Address Translator RFC 3031 Multiprotocol Label Switching Architecture RFC 3032 MPLS Label Stack Encoding RFC 3036 LDP Specification RFC 3046 DHCP Relay Agent Information Option RFC 3063 MPLS Loop Prevention Mechanism RFC 3065 Support AS confederation RFC 3137 OSPF Stub Router Advertisement RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP) RFC 3214 LSP Modification Using CR-LDP RFC 3215 LDP State Machine RFC 3246 Expedited Forwarding PHB RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS) RFC 3277 IS-IS Transient Blackhole Avoidance RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile RFC 3392 Support BGP capabilities advertisement RFC 3410 Introduction and Applicability Statements for Internet Standard Management Framework

Standards and Protocols

(applies to all products in series)

	<p>RFC 1144 Compressing TCP/IP headers for low-speed serial links</p> <p>RFC 1195 OSI ISIS for IP and Dual Environments</p> <p>RFC 1256 ICMP Router Discovery Protocol (IRDP)</p> <p>RFC 1293 Inverse Address Resolution Protocol</p> <p>RFC 1315 Management Information Base for Frame Relay DTEs</p> <p>RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)</p> <p>RFC 1333 PPP Link Quality Monitoring</p> <p>RFC 1334 PPP Authentication Protocols (PAP)</p> <p>RFC 1349 Type of Service</p> <p>RFC 1350 TFTP Protocol (revision 2)</p> <p>RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)</p> <p>RFC 1381 SNMP MIB Extension for X.25 LAPB</p> <p>RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol</p> <p>RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol</p> <p>RFC 1490 Multiprotocol Interconnect over Frame Relay</p> <p>RFC 1519 CIDR</p> <p>RFC 1534 DHCP/BOOTP Interoperation</p> <p>RFC 1542 Clarifications and Extensions for the Bootstrap Protocol</p> <p>RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)</p> <p>RFC 1577 Classical IP and ARP over ATM</p> <p>RFC 1613 Cisco Systems X.25 over TCP (XOT)</p> <p>RFC 1624 Incremental Internet Checksum</p> <p>RFC 1631 NAT</p> <p>RFC 1638 PPP Bridging Control Protocol (BCP)</p> <p>RFC 1661 The Point-to-Point Protocol (PPP)</p> <p>RFC 1662 PPP in HDLC-like Framing</p> <p>RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMiv2</p>	<p>RFC 2364 PPP Over AAL5</p> <p>RFC 2374 An Aggregatable Global Unicast Address Format</p> <p>RFC 2451 The ESP CBC-Mode Cipher Algorithms</p> <p>RFC 2453 IPv2</p> <p>RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols</p> <p>RFC 2511 Internet X.509 Certificate Request Message Format</p> <p>RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)</p> <p>RFC 2570 Introduction to Version 3 of the Internet-standard Network Management Framework</p> <p>RFC 2644 Directed Broadcast Control</p> <p>RFC 2661 L2TP</p> <p>RFC 2663 NAT Terminology and Considerations</p> <p>RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5</p> <p>RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)</p> <p>RFC 2702 Requirements for Traffic Engineering Over MPLS</p> <p>RFC 2747 RSVP Cryptographic Authentication</p> <p>RFC 2763 Dynamic Name-to-System ID mapping support</p> <p>RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)</p> <p>RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)</p> <p>RFC 2784 Generic Routing Encapsulation (GRE)</p> <p>RFC 2787 Definitions of Managed Objects for VRRP</p> <p>RFC 2961 RSVP Refresh Overhead Reduction Extensions</p> <p>RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS</p> <p>RFC 2973 IS-IS Mesh Groups</p> <p>RFC 2985 PKCS #9: Selected Object Classes and Attribute Types Version 2.0</p> <p>RFC 2993 Architectural Implications of NAT</p>	<p>RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)</p> <p>RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering</p> <p>RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPSec</p> <p>RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers</p> <p>RFC 3784 ISIS TE support</p> <p>RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit</p> <p>RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management</p> <p>RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)</p> <p>RFC 3847 Restart signaling for IS-IS</p> <p>RFC 4301 Security Architecture for the Internet Protocol</p> <p>RFC 5101 Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of IP Traffic Flow Information</p> <p>FRF.1.2 PVC User-to-Network Interface (UNI) Implementation Agreement—July 2000</p> <p>FRF.11.1 Voice over Frame Relay Implementation Agreement—May 1997—Annex J added March 1999</p> <p>FRF.12 Frame Relay Fragmentation Implementation Agreement—December 1997</p> <p>FRF.16.1 Multilink Frame Relay UNI/NNI Implementation Agreement—May 2002</p> <p>FRF.2.2 Frame Relay Network-to-Network Interface (NNI) Implementation Agreement—March 2002</p> <p>FRF.20 Frame Relay IP Header Compression Implementation Agreement—June 2001</p> <p>FRF.3.2 Frame Relay Multiprotocol Encapsulation Implementation Agreement—April 2000</p> <p>FRF.7 Frame Relay PVC Multicast Service and Protocol Description—October 1994</p> <p>FRF.9 Data Compression Over Frame Relay Implementation Agreement—January 1996</p>
IP multicast	<p>RFC 1112 IGMP</p> <p>RFC 2236 IGMPv2</p>	<p>RFC 2283 Multiprotocol Extensions for BGP-4</p> <p>RFC 2362 PIM Sparse Mode</p>	<p>RFC 2934 Protocol Independent Multicast MIB for IPv4</p> <p>RFC 3376 IGMPv3</p>

Standards and Protocols

(applies to all products in series)

IPv6	RFC 1981 IPv6 Path MTU Discovery RFC 2080 RIPng for IPv6 RFC 2292 Advanced Sockets API for IPv6 RFC 2373 IPv6 Addressing Architecture RFC 2460 IPv6 Specification RFC 2461 IPv6 Neighbor Discovery RFC 2462 IPv6 Stateless Address Auto-configuration RFC 2463 ICMPv6	RFC 2464 Transmission of IPv6 over Ethernet Networks RFC 2472 IP Version 6 over PPP RFC 2473 Generic Packet Tunneling in IPv6 RFC 2529 Transmission of IPv6 Packets over IPv4 RFC 2545 Use of MP-BGP-4 for IPv6 RFC 2553 Basic Socket Interface Extensions for IPv6	RFC 2740 OSPFv3 for IPv6 RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers RFC 3056 Connection of IPv6 Domains via IPv4 Clouds RFC 3513 IPv6 Addressing Architecture RFC 3596 DNS Extension for IPv6
MIBs	RFC 1213 MIB II RFC 1229 Interface MIB Extensions RFC 1286 Bridge MIB RFC 1493 Bridge MIB RFC 1573 SNMP MIB II RFC 1724 RIPv2 MIB RFC 1757 Remote Network Monitoring MIB	RFC 1850 OSPFv2 MIB RFC 2011 SNMPv2 MIB for IP RFC 2012 SNMPv2 MIB for TCP RFC 2013 SNMPv2 MIB for UDP RFC 2233 Interfaces MIB RFC 2454 IPV6-UDP-MIB RFC 2465 IPV6 MIB RFC 2466 ICMPv6 MIB	RFC 2618 RADIUS Client MIB RFC 2620 RADIUS Accounting MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB RFC 2737 Entity MIB (Version 2) RFC 2863 The Interfaces Group MIB RFC 2933 IGMP MIB RFC 3813 MPLS LSR MIB
Network management	IEEE 802.1D (STP) RFC 1155 Structure of Management Information RFC 1157 SNMPv1	RFC 1905 SNMPv2 Protocol Operations RFC 2272 SNMPv3 Management Protocol RFC 2273 SNMPv3 Applications RFC 2274 USM for SNMPv3	RFC 2275 VACM for SNMPv3 RFC 2575 SNMPv3 View-based Access Control Model (VACM) RFC 3164 BSD syslog Protocol
OSPF	RFC 1245 OSPF protocol analysis RFC 1246 Experience with OSPF RFC 1587 OSPF NSSA	RFC 1765 OSPF Database Overflow RFC 1850 OSPFv2 Management Information Base (MIB), traps	RFC 2328 OSPFv2 RFC 2370 OSPF Opaque LSA Option RFC 3101 OSPF NSSA
QoS/CoS	IEEE 802.1P (CoS) RFC 2474 DS Field in the IPv4 and IPv6 Headers	RFC 2475 DiffServ Architecture RFC 2597 DiffServ Assured Forwarding (AF)	RFC 2598 DiffServ Expedited Forwarding (EF) RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
Security	IEEE 802.1X Port Based Network Access Control RFC 1321 The MD5 Message-Digest Algorithm RFC 2082 RIP-2 MD5 Authentication RFC 2104 Keyed-Hashing for Message Authentication	RFC 2138 RADIUS Authentication RFC 2209 RSVP-Message Processing RFC 2246 Transport Layer Security (TLS) RFC 2716 PPP EAP-TLS Authentication Protocol	RFC 2865 RADIUS Authentication RFC 2866 RADIUS Accounting RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
VPN	RFC 2403 - HMAC-MD5-96 RFC 2404 - HMAC-SHA1-96 RFC 2405 - DES-CBC Cipher algorithm RFC 2547 BGP/MPLS VPNs	RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP RFC 2842 Capabilities Advertisement with BGP-4 RFC 2858 Multiprotocol Extensions for BGP-4	RFC 2918 Route Refresh Capability for BGP-4 RFC 3107 Carrying Label Information in BGP-4
IPSec	RFC 1828 IP Authentication using Keyed MD5 RFC 2401 IP Security Architecture RFC 2402 IP Authentication Header	RFC 2406 IP Encapsulating Security Payload RFC 2407 - Domain of interpretation RFC 2410 - The NULL Encryption Algorithm and its use with IPSec	RFC 2411 IP Security Document Roadmap RFC 2412 - OAKLEY RFC 2865 - Remote Authentication Dial In User Service (RADIUS)
IKEv1		RFC 2865 - Remote Authentication Dial In User Service (RADIUS)	RFC 3748 - Extensible Authentication Protocol (EAP)

HP MSR50 Series accessories

Transceivers

HP X110 100M SFP LC FX Transceiver (JD102B)
 HP X110 100M SFP LC LX Transceiver (JD120B)
 HP X110 100M SFP LC LH40 Transceiver (JD090A)
 HP X110 100M SFP LC LH80 Transceiver (JD091A)
 HP X120 1G SFP LC SX Transceiver (JD118B)
 HP X120 1G SFP LC LX Transceiver (JD119B)
 HP X125 1G SFP LC LH40 1310nm Transceiver (JD061A)
 HP X120 1G SFP LC LH40 1550nm Transceiver (JD062A)
 HP X125 1G SFP LC LH70 Transceiver (JD063B)
 HP X120 1G SFP LC LH100 Transceiver (JD103A)
 HP X120 1G SFP LC BX 10-U Transceiver (JD098B)
 HP X120 1G SFP LC BX 10-D Transceiver (JD099B)

Cables

HP X200 V.24 DTE 3m Serial Port Cable (JD519A)
 HP X200 V.24 DCE 3m Serial Port Cable (JD521A)
 HP X200 V.35 DTE 3m Serial Port Cable (JD523A)
 HP X200 V.35 DCE 3m Serial Port Cable (JD525A)
 HP X260 RS449 3m DTE Serial Port Cable (JF825A)
 HP X260 RS449 3m DCE Serial Port Cable (JF826A)
 HP X260 RS530 3m DTE Serial Port Cable (JF827A)
 HP X260 RS530 3m DCE Serial Port Cable (JF828A)
 HP X260 Auxiliary Router Cable (JD508A)
 HP X260 E1 RJ45 3m Router Cable (JD509A)
 HP X260 E1 RJ45 20m Router Cable (JD517A)
 HP X260 E1 (2) BNC 75 ohm 3m Router Cable (JD175A)
 HP X260 E1 BNC 20m Router Cable (JD514A)
 HP X260 E1 2 BNC 75 ohm 40m Router Cable (JD516A)
 HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable (JD511A)
 HP X260 2E1 BNC 3m Router Cable (JD643A)
 HP X260 T1 Router Cable (JD518A)
 HP X260 T3/E3 Router Cable (JD531A)
 HP X260 E3-30 E3/T3 Router Cable (JD533A)
 HP X260 E1 4-port IMA Router Cable (JD638A)
 HP X260 8E1 BNC 75 ohm 3m Router Cable (JD512A)
 HP X260 SIC-8A5 RJ45 0.28m Router Cable (JD642A)
 HP X200 Transit Plug D25F MP8(S) Single Cable (JD636A)
 HP X200 Transit RJ45 0.5m Single Cable (JD641A)
 HP X260 mini D-28 to 4-RJ45 0.3m Router Cable (JG263A)
 HP MSR 50 pin D-sub Male to 24 x RJ-11 Plug 15m Router Cable (JG318A)
 HP CAB-75ohm 8E1-3m-BNC-IMA (JD927A)
 HP X260 8T1 RJ45 3m Router Cable (JD639A)

Power Supply

HP MSR50 350W AC Power Supply (JD650A)
 HP MSR50 350W DC Power Supply (JF443A)
 HP MSR50 500W PoE Power Module (JD652A)

License

HP MSR50 Series Standard Version Router Software License (JD434A)

HP MSR50 Series accessories (continued)

Router Modules

HP MSR50 G2 Main Processing Unit (JD429B)
 HP MSR50 G2 Multi-Service Module (JD430A)
 HP MSR50 Main Processing Unit (JD653A)
 HP MSR50 Multi-Service Module (JD651A)
 HP MSR Encryption Accelerator Advanced Module (JD608A)
 HP MSR Standard Encryption Accelerator Module (JD609A)
 HP MSR Voice Co-processor Module (JD610A)
 HP MSR 32-channel Voice Processor Module (JD598A)
 HP MSR 24-channel Voice Processor Module (JD599A)
 HP MSR 9-port 10/100Base-T Switch DSIC Module (JD574B)
 HP MSR 9-port 10/100Base-T PoE Switch DSIC Module (JD621A)
 HP MSR 4-port 10/100Base-T Switch SIC Module (JD573B)
 HP MSR 4-port 10/100Base-T PoE Switch SIC Module (JD620A)
 HP MSR 1-port 10/100Base-T SIC Module (JD545B)
 HP MSR 1-port 100Base-X SIC Module (JF280A)
 HP MSR 1-port GbE Combo SIC Module (JD572A)
 HP MSR 2-port FXO SIC Module (JD558A)
 HP MSR 2-port FXS SIC Module (JD560A)
 HP MSR 2-port ISDN-S/T Voice SIC Module (JF821A)
 HP MSR 2-port FXS/1-port FXO SIC Module (JD632A)
 HP MSR 1-port E1 Voice SIC Module (JD575A)
 HP MSR 1-port T1 Voice SIC Module (JD576A)
 HP MSR 1-port E1/Fractional E1 (75ohm) SIC Module (JD634B)
 HP MSR 2-port E1/Fractional E1 (75ohm) SIC Module (JF842A)
 HP MSR 1-port T1/Fractional T1 SIC Module (JD538A)
 HP MSR 1-port ADSL2+ SIC Module (JD537A)
 HP MSR 1-port ADSL over ISDN SIC Module (JG056B)
 HP MSR 1-port 8-wire G.SHDSL (RJ45) DSIC Module (JG191A)
 HP MSR 1-port Enhanced Serial SIC Module (JD557A)
 HP MSR 1-port ISDN-S/T SIC Module (JD571A)
 HP MSR 8-port Async Serial SIC Module (JF281A)
 HP MSR 16-port Async Serial SIC Module (JG186A)
 HP MSR 802.11b/g/n Wireless Access Point SIC Module (JF819A)
 HP MSR 802.11b/g/n Wireless Access Point SIC Module (NA) (JG211A)
NEW HP MSR 4G LTE SIC Module for Verizon/LTE 700 MHz/CDMA Rev A (JG742A)
NEW HP MSR 4G LTE SIC Module for ATT/LTE 700/1700/2100 MHz and UMTS/HSPA+/HSPA/EDGE/GRPS/GSM (JG743A)
NEW HP MSR 4G LTE SIC Module for Global/LTE 800/900/1800/2100/2600 MHz and UMTS/HSPA+/HSPA/EDGE/GRPS/GSM (JG744A)
 HP MSR 4-port 10/100Base-T FIC Module (JF824A)
 HP MSR 2-port 10/100Base-T FIC Module (JD577A)
 HP MSR 1-port Gig-T FIC Module (JD583B)
 HP MSR 1-port 1000Base-X FIC Module (JD582A)
 HP MSR 2-port Gig-T FIC Module (JF269B)
 HP MSR 2-port 1000BASE-X FIC Module (JF270B)
 HP MSR 8-port Enhanced Sync/Async Serial FIC Module (JD580A)
 HP MSR 4-port Enhanced Sync/Async Serial FIC Module (JD584A)
 HP MSR 8-port Enhanced Async Serial FIC Module (JF260B)
 HP MSR 16-port Enhanced Async Serial FIC Module (JF265B)
 HP MSR 4-port FXO FIC Module (JD593A)

HP MSR50 Series accessories (continued)

Router Modules

HP MSR 4-port FXS FIC Module (JD594A)
 HP MSR 4-port E&M FIC Module (JD602A)
 HP MSR 2-port E1 Voice FIC Module (JD587A)
 HP MSR 1-port E1 Voice FIC Module (JD607A)
 HP MSR 2-port T1 Voice FIC Module (JD606A)
 HP MSR 1-port T1 Voice FIC Module (JD605A)
 HP MSR 8-port E1/CE1/PRI (75ohm) FIC Module (JD585A)
 HP MSR 4-port E1/CE1/PRI FIC Module (JD588A)
 HP MSR 2-port E1/CE1/PRI FIC Module (JD578A)
 HP MSR 4-port E1/Fractional E1 FIC Module (JD591A)
 HP MSR 4-port T1/Fractional T1 FIC Module (JD592A)
 HP MSR 1-port E3/CE3/FE3 FIC Module (JD625A)
 HP MSR 1-port FT3/CT3 FIC Module (JD629A)
 HP MSR 1-port E3 ATM FIC Module (JD596A)
 HP MSR 1-port T3 ATM FIC Module (JD595A)
 HP MSR 4-port E1 IMA (75ohm) FIC Module (JD622A)
 HP MSR 4-port Enhanced ISDN-S/T FIC Module (JD589A)
 HP MSR 1-port OC-3c/STM-1c ATM SFP FIC Module (JD633A)
 HP MSR 1-port OC-3c/STM-1c POS FIC Module (JD581C)
 HP MSR 1-port OC-3/STM-1 (E1/T1) CPOS FIC Module (JG201A)
 HP MSR 24-port FXS FIC Module (JG197A)
 HP MSR 8-port T1/CT1/PRI FIC Module (JD586B)
 HP MSR 8-port T1 IMA FIC Module (JG200A)
 HP MSR 8-port E1 IMA (75ohm) FIC Module (JF278B)
 HP MSR 1-port E1/CE1/PRI SIC Module (JF253B)
 HP MSR 4-port FXS / 1-port FXO DSIC Module (JG189A)
 HP MSR HSPA/WCDMA SIC Module (JG187A)
 HP MSR Open Application Platform (OAP) with VMware vSphere FIC Module (JG533A)

Memory

HP MSR 512MB SDRAM (JD648A)
 HP 2GB DDR2 SDRAM Memory (JG205A)
 HP X600 1G Compact Flash Card (JC684A)
 HP X600 512M Compact Flash Card (JC685A)
 HP X600 256M Compact Flash Card (JC686A)

Telephony modules

HP MSR Large Survivable Branch Communication FIC Module powered by Microsoft Lync (JG589A)

Learn more at
hp.com/networking

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2010-2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft is a U.S. registered trademark of the Microsoft group of companies.

4AA3-0767ENW, July 2014, Rev. 6

